

Product reference	開口(オープニング)	開口率	経糸	横糸	経糸	横糸	経糸	横糸	重量	重量	厚さ	幅	特注幅
	[μm]	[%]	[n/cm]	[n/cm]	[n/インチ(標準)規格単位]	[n/インチ(標準)規格単位]	[μm]	[μm]	[g/m ² (標準)規格単位]	[oz/yd ²]	[μm]	[cm]	[cm]
03-100/32	100	32	57.0	57.0	145	145	77	77	55	1.6	125	98 115 158	-
03-100/44	100	44	66.0	66.0	168	168	51	51	30	0.9	80	102	-
03-103/39	103	39	62.0	62.0	157	157	62	62	45	1.3	105	102 153	-
03-110/47	110	47	62.0	62.0	157	157	51	51	31	0.9	75	102	-
03-118/42	118	42	51.0	60.0	130	152	60	50	34	1.0	115	-	115
03-120/34	120	34	49.0	49.0	124	124	85	85	60	1.8	145	122	-
03-120/49	120	49	59.0	59.0	150	150	51	51	28	0.8	80	102	-
03-125/37	125	37	48.8	48.8	124	124	85	85	62	1.8	137	136	-
03-125/39	125	39	50.0	50.0	127	127	75	75	50	1.5	135	102	-
03-125/45	125	45	53.0	53.0	135	135	62	62	43	1.3	100	102	-
03-130/52	130	52	56.0	56.0	142	142	50	50	21	0.6	80	102	-
03-132/40	132	40	45.0	45.0	114	114	83	83	50	1.5	130	115	-
03-132/43	132	43	49.0	49.0	124	124	75	75	49	1.4	125	-	158
03-140/37	140	37	44.0	44.0	112	112	95	95	65	1.9	159	115	-
03-140/41	140	41	45.0	45.0	114	114	83	83	50	1.5	130	-	158
03-150/38	150	38	41.0	41.0	104	104	95	95	60	1.8	155	102 115 136 153	-
03-150/50	150	50	47.0	47.0	119	119	62	62	35	1.0	95	102	-
03-151/42	151	42	43.0	43.0	109	109	83	83	55	1.6	145	115	-
03-160/37	160	37	37.0	37.0	94	94	105	105	75	2.2	165	115	-
03-160/53	160	53	45.0	45.0	114	114	61	61	34	1.0	100	102	-
03-165/44	165	44	41.0	41.0	104	104	83	83	50	1.5	140	102 158	-
03-170/54	170	54	43.0	43.0	109	109	62	62	32	0.9	100	102	-
03-175/39	175	39	36.0	36.0	91	91	105	105	70	2.1	165	-	115
03-177/34	177	34	33.0	33.0	84	84	125	125	108	3.2	220	115 158	-
03-180/44	180	44	37.0	37.0	94	94	93	93	64	1.9	155	102	-
03-190/57	190	57	40.0	40.0	102	102	62	62	30	0.9	100	102	-
03-200/39	200	39	30.0	30.0	76	76	122	122	85	2.5	225	115	136
03-200/45	200	45	32.0	32.0	81	81	105	105	60	1.8	185	102	-
03-200/47	200	47	34.0	34.0	86	86	92	92	60	1.8	150	102	158
03-200/48	200	48	34.0	34.0	86	86	80	80	43	1.3	185	136	-
03-200/54	200	54	37.0	37.0	94	94	73	73	37	1.1	125	102	-
06-210/33	210	33	28.0	28.0	71	71	155	155	105	3.1	275	100	158
03-210/40	210	40	30.0	30.0	76	76	122	122	85	2.5	215	-	115
03-225/42	225	42	29.0	29.0	74	74	122	122	80	2.4	200	-	115
03-236/44	236	44	28.0	28.0	71	71	122	122	77	2.3	210	-	115
06-240/37	240	37	25.0	25.0	64	64	155	155	85	2.5	290	-	115
03-240/44	240	44	28.0	28.0	71	71	122	122	75	2.2	220	-	196
06-250/34	250	34	23.0	23.0	58	58	170	170	130	3.8	290	102 142	-
03-250/50	250	50	29.0	29.0	74	74	103	103	55	1.6	170	102	-
03-255/46	255	46	27.0	27.0	69	69	122	122	75	2.2	205	115	-
06-275/44	275	44	24.0	24.0	61	61	155	155	84	2.5	255	-	115
06-280/45	280	45	24.0	24.0	61	61	155	155	83	2.5	255	115	-
03-280/51	280	51	25.0	25.0	64	64	122	122	70	2.1	210	-	158
06-300/34	300	34	20.0	20.0	51	51	215	215	170	5.0	390	115 186	-

Product reference	開口(オープニング)	開口率	経糸	横糸	経糸	横糸	経糸	横糸	重量	重量	厚さ	幅	特注幅
	[μm]	[%]	[n/cm]	[n/cm]	[n/インチ(標準)規格単位]	[n/インチ(標準)規格単位]	[μm]	[μm]	[g/m ² (標準)規格単位]	[oz/yd ²]	[μm]	[cm]	[cm]
03-300/51	300	51	24.0	24.0	61	61	122	122	75	2.2	200	102 112 153	-
06-310/45	310	45	22.0	22.0	56	56	151	151	92	2.7	250	115	136
06-315/44	315	44	21.0	21.0	53	53	180	180	102	3.0	300	115	-
06-335/46	335	46	20.0	20.0	51	51	168	168	100	3.0	300	-	115
06-350/35	350	35	17.0	17.0	43	43	240	240	170	5.0	400	103	-
06-350/42	350	42	18.5	18.5	47	47	190	190	110	3.3	330	115	-
06-355/48	355	48	19.0	19.0	48	48	180	180	94	2.8	300	115 136	-
06-390/47	390	47	18.0	18.0	46	46	190	190	140	4.1	310	-	136
06-400/38	400	38	15.0	15.0	38	38	250	250	180	5.3	450	106	-
06-405/47	405	47	17.0	17.0	43	43	190	190	110	3.3	330	-	115
06-425/46	425	46	16.0	16.0	41	41	205	205	130	3.8	365	115	-
06-430/38	430	38	14.0	14.0	36	36	272	272	200	5.9	510	-	152
06-450/48	450	48	15.0	15.0	38	38	205	205	125	3.7	360	115 158	-
06-475/56	475	56	16.0	16.0	41	41	180	180	85	2.5	290	108	-
06-500/38	500	38	12.0	12.0	30	30	315	315	225	6.7	580	115 158	-
06-500/47	500	47	14.0	14.0	36	36	225	225	130	3.8	375	136	-
06-530/50	530	50	13.0	13.0	33	33	230	230	130	3.8	400	-	158
06-600/41	600	41	11.0	11.0	28	28	335	335	235	7.0	630	115	-
06-600/51	600	51	12.0	12.0	30	30	245	245	135	4.0	440	115	-
06-600/59	600	59	13.0	13.0	33	33	180	180	80	2.4	350	-	158
06-670/53	670	53	11.0	11.0	28	28	272	272	136	4.0	475	-	115
06-700/44	700	44	10.0	10.0	25	25	355	355	225	6.7	650	112	-
06-700/53	700	53	11.0	11.0	28	28	265	265	140	4.1	485	115	-
06-750/52	750	52	9.5	9.5	24	24	290	290	140	4.1	495	115	-
06-780/53	780	53	9.4	9.4	24	24	290	290	140	4.1	550	115	-
06-850/46	850	46	8.0	8.0	20	20	405	405	255	7.5	800	109	-
06-950/57	950	57	8.0	8.0	20	20	305	305	140	4.1	560	-	112
06-1000/44	1000	44	6.7	6.7	17	17	515	515	330	9.8	890	110 142	-
06-1000/57	1000	57	7.5	7.5	19	19	330	330	150	4.4	605	108	-
06-1140/66	1140	66	7.1	7.1	18	18	265	265	93	2.7	490	-	158
06-1180/59	1180	59	6.5	6.5	17	17	360	360	160	4.7	650	110	-
06-1320/59	1320	59	5.8	5.8	15	15	405	405	190	5.6	770	108	-
06-1400/49	1400	49	5.0	5.0	13	13	610	610	340	10.1	1160	158	102 180
06-1550/60	1550	60	5.0	5.0	13	13	450	450	185	5.5	790	108	-
06-1700/50	1700	50	4.2	4.2	11	11	695	695	385	11.4	1300	104	-
06-1800/61	1800	61	4.4	4.4	11	11	500	500	200	5.9	910	-	115
06-2000/53	2000	53	3.6	3.6	9	9	750	750	380	11.2	1325	102 158	-
06-2400/55	2400	55	3.1	3.1	8	8	850	850	415	12.3	1500	102	183
06-3300/59	3300	59	2.3	2.3	6	6	1000	1000	460	13.6	1860	190	102
06-5000/72	5000	72	1.7	1.7	4	4	900	900	270	8.0	1680	-	115

SEFAR NITEX®

お問い合わせ  Ring

 072-990-1305 |  FAX 072-990-1303 |  info@ring-gr.jp