

Product reference	開口(オープニング)	開口率	経糸	横糸	経糸	横糸	経糸	横糸	重量	重量	厚さ	幅	特注幅
	[μm]	[%]	[n/cm]	[n/cm]	[n/インチ(標準)規格単位]	[n/インチ(標準)規格単位]	[μm]	[μm]	[g/m ² (標準)規格単位]	[oz/yd ²]	[μm]	[cm]	[cm]
07-170/41	170	41	38.0	38.0	97	97	96	96	70	2.1	150	102	-
07-180/31	180	31	30.5	30.5	77	77	147	147	130	3.8	250	102	150
07-180/46	180	46	35.7	35.7	91	91	64	64	51	1.5	142	-	136
07-200/39	200	39	31.0	31.0	79	79	121	121	100	3.0	215	110	-
07-200/43	200	43	33.0	33.0	84	84	104	104	75	2.2	170	150	115
07-210/35	210	35	28.0	28.0	71	71	147	147	135	4.0	250	154	-
07-230/43	230	43	28.5	28.5	72	72	122	122	90	2.7	215	-	130
07-240/59	240	59	32.0	32.0	81	81	73	73	35	1.0	115	118	-
07-250/39	250	39	24.5	24.5	62	62	152	152	140	4.1	290	145	-
07-250/46	250	46	27.0	27.0	69	69	122	122	95	2.8	203	115	-
07-265/47	265	47	26.0	26.0	66	66	122	122	85	2.5	200	-	115 150
07-285/44	285	44	24.0	24.0	61	61	145	145	110	3.3	260	-	102
07-285/55	285	55	26.0	26.0	66	66	103	103	60	1.8	168	102	-
07-300/36 TBA190	300	36	20.0	20.0	51	51	205	205	180	5.3	405	203	-
07-300/36	300	36	20.0	20.0	51	51	205	205	180	5.3	405	115	-
07-300/46	300	46	22.5	22.5	57	57	143	143	95	2.8	245	100	-
07-315/44	315	44	21.0	21.0	53	53	165	165	119	3.5	285	115	-
07-335/46	335	46	20.2	20.2	51	51	165	165	120	3.6	280	-	136
07-350/34	350	34	16.7	16.7	42	42	250	250	234	6.9	505	158	-
07-355/47	355	47	19.4	19.4	49	49	165	165	115	3.4	375	136	-
07-375/46	375	46	18.0	18.0	46	46	188	188	125	3.7	330	-	115
07-400/48	400	48	17.2	17.2	44	44	188	188	115	3.4	335	115	136 158
07-420/39	420	39	15.0	15.0	38	38	250	250	210	6.2	500	-	265
07-425/46	425	46	16.0	16.0	41	41	200	200	155	4.6	355	136	115
07-450/48	450	48	15.4	15.4	39	39	200	200	150	4.4	350	-	115 136
07-465/49	465	49	15.0	15.0	38	38	200	200	135	4.0	365	-	136
07-500/39	500	39	12.5	12.5	32	32	300	300	255	7.5	620	142	-
07-500/48	500	48	14.0	14.0	36	36	220	220	150	4.4	410	115	-
07-560/49	560	49	12.5	12.5	32	32	250	250	175	5.2	450	136	-
07-600/51	600	51	12.0	12.0	30	30	245	245	165	4.9	450	115	158
07-670/52	670	52	10.7	10.7	27	27	265	265	175	5.2	475	158	-
07-710/45	710	45	9.4	9.4	24	24	350	350	250	7.4	745	-	158
07-710/54	710	54	10.3	10.3	26	26	260	260	170	5.0	465	115	136
07-800/48	800	48	8.7	8.7	22	22	350	350	128	3.8	680	-	180
07-800/55	800	55	9.0	9.0	23	23	280	280	165	4.9	520	115	-
07-840/46	840	46	8.0	8.0	20	20	400	400	280	8.3	785	110	-
07-850/55	850	55	8.7	8.7	22	22	300	300	190	5.6	600	-	136
07-900/56	900	56	8.3	8.3	21	21	300	300	180	5.3	575	-	136
07-950/58	950	58	8.0	8.0	20	20	300	300	175	5.2	575	-	136

Product reference	開口(オープニング) [μm]	開口率 [%]	メッシュ 経糸 [n/cm]	メッシュ 横糸 [n/cm]	メッシュ 経糸 [n/インチ(標準)規格単位]	メッシュ 横糸 [n/インチ(標準)規格単位]	線径 経糸 [μm]	線径 横糸 [μm]	重量 [g/m ² (標準)規格単位]	重量 [oz/yd ²]	厚さ [μm]	幅 [cm]	特注幅 [cm]
07-1000/45TBA200	1000	45	6.7	6.7	17	17	500	500	400	11.8	1000	125 145 167 183 202 226 253 305	-
07-1000/45 HD	1000	45	6.7	6.7	17	17	500	500	400	11.8	1000	320	-
07-1000/58	1000	58	7.6	7.6	19	19	320	320	185	5.5	585	115 136	-
07-1180/60	1180	60	6.5	6.5	17	17	350	350	175	5.2	740	-	110
07-1190/47	1190	47	5.7	5.7	14	14	550	550	397	11.7	1010	-	142
07-1320/59	1320	59	5.8	5.8	15	15	400	400	200	5.9	740	109	-
07-1410/49	1410	49	5.0	5.0	13	13	600	600	420	12.4	1145	158	-
07-1600/61	1600	61	4.9	4.9	12	12	450	450	236	7.0	840	115	-
07-1680/50	1680	50	4.2	4.2	11	11	700	700	465	13.8	1300	158	-
07-1800/61	1800	61	4.3	4.3	11	11	500	500	245	7.2	1000	110 142	-
07-2000/51	2000	51	3.6	3.6	9	9	800	800	552	16.3	1500	104 158	201
07-2200/47 blue	2200	47	3.2	3.2	8	8	1000	1000	760	22.5	1860	210	-
07-2380/53	2380	53	3.1	3.1	8	8	900	900	600	17.8	1700	104 158	-
07-3000/62	3000	62	2.6	2.6	7	7	800	800	385	11.4	1480	102	-
07-3000/62 TBA190	3000	62	2.6	2.6	7	7	800	800	385	11.4	1480	-	165
07-3400/60	3400	60	2.3	2.3	6	6	1000	1000	500	14.8	1900	220	-
07-4000/64	4000	64	2.0	2.0	5	5	1000	1000	460	13.6	1900	108 158	-
07-5000/72	5000	72	1.7	1.7	4	4	900	900	320	9.5	1700	158	-

お問い合わせ



☎ 072-990-1305 | FAX 072-990-1303 | ✉ info@ring-gr.jp